CE 603 Homework 1 Satellite Camera Radiometry Spring 2007

Design an 0.4 meter GSD, panchromatic satellite camera for low earth orbit (400-2000 km). Give recommendation for the following and show how you arrived at your values:

- Altitude
- Focal length
- Aperture diameter
- Cycle time (line rate) and exposure time
- Camera rotation rate required during scene capture

Use three of Kodak KLI 8811 linear arrays to obtain an effective cross track sampling of 24,000 pixels. We want to obtain a nominally square scene (24k x 24k pixels). We would also like to obtain in-track stereo with B/H of 0.6. Ensure that each scene is acquired in 10 seconds and that 20 seconds are allowed between each scene of the stereo pair for repositioning. Accommodate scene elements with 70% reflectance. Use quantum efficiency of 30% and noise factor K = 0.7 (30% loss). Assume that this sensor can be configured with 32 TDI stages.

Steps:

- Integrate planck function over visible wavelengths to get solar radiance
- Use $M = \pi L \varepsilon$, to get emittance, use 0.99 for emissivity
- Use area of sun surface to get total flux emitted in the visible
- Get E_e irradiance at earth (top of atmosphere) by total flux divided by area of sphere at sun-earth distance
- M_e apparent emittance of brightest scene element by multiplying the prior E_e by 70% max reflectance and by 2x atmospheric attenuation factor 0.64²
- Get radiance of that scene element by $L = M_e / \pi$
- Use green light (550 nm) to obtain energy per photon (*hv*) and use the full well (saturation) level to get max energy per detector (Q)
- Use max scan time to get line rate, get T_e and extended T_e via TDI stages.
- Use the design equation $Q = q_e k L \pi R_a^2 \frac{1}{A l t^2} T_e S^2$ to make a table of possible

aperture and altitude values. Choose the smallest aperture as the solution.

References

- IRIS tutorial on course web page
- Rees, W.G., 2001, Physical Principals of Remote Sensing, Cambridge Univ. Press
- Elachi, C., 1987, Introduction to the Physics and Techniques of Remote Sensing, John Wiley & sons
- <u>www.kodak.com</u> / all businesses / image sensor solutions / products / linear CCD / KLI 8811 / specifications / product summary & data sheet